



## OUR LATEST INNOVATION

In Advanced Workforce Management



The TouchTime® III provides the most sophisticated employee self-service capabilities available—all designed to automate many processes and minimize time-consuming manual data entry for human resource and operations departments.

An updated Windows 10 operating system and multiple modular peripheral configuration options offer the ultimate flexibility. Application development and deployment are now even simpler with CMI's loading and monitoring system.

A touch-screen tablet allows employees to access an array of data including work schedules, salary accruals, vacation updates and more. They can also submit information such as the results of their shifts, vacation requests and benefits modifications.

**The TouchTime III**  
is ready to work for you with:



#### Windows 10 Operating System

- Familiar User Interface
- Runs Java, .Net, & Browser-Based Applications



#### Easy Network Connectivity

- WiFi
- Bluetooth
- Power Over Ethernet



#### Employee Auto-Identification Peripherals

- RFID Proximity Card Reader
- Fingerprint Scanner
- Facial Recognition

## FEATURES & SPECIFICATIONS

#### OS/Memory & Processor

- Windows 10 IoT Enterprise LTSB (64 Bit)
- 64 GB SSD, 8 GB Flash, 2 GB RAM Internal Storage
- Intel Atom™ X5-E8000 Quad Core

#### User and Communication Interface

- 10.1" 5-Finger Capacitive-Touch Display
  - Aspect Ratio: 16:9
  - Resolution: 1280 x 800 Pixels
- Wi-Fi (802.11a/b/g/n)
- Bluetooth 4.0 Technology
- Gigabit Ethernet

#### Physical

- 12.0 x 8.75 x 3.78 Inches
- Approximate Weight: 6.4 lbs. w/ Wall Mount & Battery

#### Cameras and A/V

- 5 MP Lens w/ High-Speed USB 2.0 Interface, 60-Degree Autofocus & 2592x1944 Max Resolution
- Intel High-Definition Audio Speakers
- Microphone



#### Auto-ID

- Barcode Reader
- Proximity Card Reader
- Magnetic Stripe Card Reader
- 2D Scanner
- Fingerprint Scanner (Suprema)

#### Environmental

- Operational Temp: 5°C to 35°C (41°F to 95°F)
- Storage -20°C to 65°C (-4°F to 149°F)
- Humidity: 20% to 80% Non-Condensing
- Electrostatic Discharge: Min. 8 KV

#### Power

- VDC: 12V 2.08A Power Pack
- Power over Ethernet: 802.3 at PoE+

#### IO Ports

- 2 External Full-Size USB 2.0